

HIGH STACTICS DUCT

ARNU07GBHA4 / ARNU09GBHA4 / ARNU12GBHA4
ARNU15GBHA4 / ARNU18GBHA4 / ARNU24GBHA4 / ARNU28GBHA4



| Model | Independent Unit | | ARNU07GBHA4 | ARNU09GBHA4 | ARNU12GBHA4 | ARNU15GBHA4 | ARNU18GBHA4 | ARNU24GBHA4 | ARNU28GBHA4 |
|---------------------------|------------------|---------------|-----------------|-----------------|-----------------|------------------|-------------------|--------------------|--------------------|
| Capacity | Cooling | Nom kW | 2.2 | 2.8 | 3.6 | 4.5 | 5.6 | 7.1 | 8.2 |
| | Heating | Nom kW | 2.5 | 3.2 | 4.0 | 5.0 | 6.3 | 8.0 | 9.2 |
| Power Input | Cooling | Nom W | 150.0 | 150.0 | 150.0 | 150.0 | 150.0 | 150.0 | 150 |
| | Heating | Nom W | 150.0 | 150.0 | 150.0 | 150.0 | 150.0 | 150.0 | 150 |
| Power Supply | | øV/Hz | 1/220-240/50,60 | 1/220-240/50,60 | 1/220-240/50,60 | 1/220-240/50,60 | 1/220-240/50,60 | 1/220-240/50,60 | 1/220-240/50,60 |
| Airflow Rate (High mode) | Cooling | H/M/L m³/min | 6.5 / 5.8 / 5.4 | 8.1 / 6.5 / 5.8 | 9.6 / 8.1 / 6.5 | 11.3 / 9.6 / 6.5 | 13.0 / 11.3 / 9.6 | 16.0 / 14.4 / 13.0 | 19.8 / 17.6 / 15.7 |
| | Heating | H/M/L m³/min | 6.5 / 5.8 / 5.4 | 8.1 / 6.5 / 5.8 | 9.6 / 8.1 / 6.5 | 11.3 / 9.6 / 6.5 | 13.0 / 11.3 / 9.6 | 16.0 / 14.4 / 13.0 | 19.8 / 17.6 / 15.7 |
| Sound Pressure | | H/M/L dBA | 34 / 33 / 32 | 36 / 35 / 33 | 37 / 35 / 34 | 39 / 37 / 34 | 40 / 38 / 37 | 42 / 41 / 40 | 43 / 41 / 40 |
| Sound Power | | H/M/L dBA | 54 / 53 / 52 | 55 / 54 / 53 | 57 / 55 / 54 | 59 / 57 / 54 | 60 / 58 / 57 | 62 / 61 / 60 | 62 / 60 / 59 |
| Dimensions | Body | WxDxH mm | 882 x 260 x 450 | 882 x 260 x 450 | 882 x 260 x 450 | 882 x 260 x 450 | 882 x 260 x 450 | 882 x 260 x 450 | 882 x 260 x 450 |
| Net Weight | | kg(lbs) | 26.0 | 26.0 | 26.0 | 26.0 | 26.5 | 26.5 | 27 |
| Piping Connection | Liquid | mm(inch) | Ø6.35 | Ø6.35 | Ø6.35 | Ø6.35 | Ø6.35 | Ø9.52 | Ø9.52 |
| | Gas | mm(inch) | Ø12.7 | Ø12.7 | Ø12.7 | Ø12.7 | Ø12.7 | Ø15.88 | Ø15.88 |
| | Drain | I.D. mm(inch) | 25 | 25 | 25 | 25 | 25 | 25 | 25 |
| Fan motor output x Number | | W | 154 x 1 | 154 x 1 | 154 x 1 | 154 x 1 | 154 x 1 | 154 x 1 | 154 |

* This product contains Fluorinated Greenhouse Gases.(R410A)

Note :

1. Capacities are based on the following conditions







Cooling - Indoor temp. 27°C(80.6°F)DB / 19°C(66.2°F)WB
Outdoor temp. 35°C(95°F)DB / 24°C(75.2°F)WB
Interconnecting piping length 7.5m
Level difference of zero

Heating - Indoor temp. 20°C(68°F)DB / 15°C(59°F)WB
Outdoor temp. 7°C(44.6°F)DB / 6°C(42.8°F)WB
Interconnecting piping length 7.5m
Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification
3. BH : The Sound Pressure test condition is based on 50 Pa (Static Pressue) as standard.
4. ID - 'Internal Diameter'

Accessories

| Model | ARNU07GBHA4 | ARNU09GBHA4 | ARNU12GBHA4 | ARNU15GBHA4 | ARNU18GBHA4 | ARNU24GBHA4 | ARNU28GBHA4 |
|-------------|--|-------------|-------------|-------------|-------------|-------------|-------------|
| Dry Contact | Simple (1 Contact point with case) | | | PDRYCB000 | | | |
| | 2 Contact point | | | PDRYCB400 | | | |
| | For Thermostat (On-off / Mode / Fan speed) | | | PDRYCB300 | | | |
| | Modbus Communication | | | PDRYCB500 | | | |

| Wired Remote Controller | | | | | Wired Remote Controller |
|---|---|---|---|---|---|
| Premium | Standard II | | Simple | Simple for Hotel | |
|  |  |  |  |  |  |
| PREMTA000 PREMTA000A PREMTA000B | PREMTB001 (White) | PREMTB001 (Black) | PQRCVCLOQ (Black) PQRCVCLOQW (White) | PQRCHCA0Q(Black) PQRCHCA0QW(White) | PQWRHQ0FDB |