

# HIGH STACTICS DUCT

ARNU07GBHA4 / ARNU09GBHA4 / ARNU12GBHA4  
ARNU15GBHA4 / ARNU18GBHA4 / ARNU24GBHA4 / ARNU28GBHA4



Model	Independent Unit		ARNU07GBHA4	ARNU09GBHA4	ARNU12GBHA4	ARNU15GBHA4	ARNU18GBHA4	ARNU24GBHA4	ARNU28GBHA4
Capacity	Cooling	Nom kW	2.2	2.8	3.6	4.5	5.6	7.1	8.2
	Heating	Nom kW	2.5	3.2	4.0	5.0	6.3	8.0	9.2
Power Input	Cooling	Nom W	150.0	150.0	150.0	150.0	150.0	150.0	150
	Heating	Nom W	150.0	150.0	150.0	150.0	150.0	150.0	150
Power Supply		øV/Hz	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60
Airflow Rate (High mode)	Cooling	H/M/L m³/min	6.5 / 5.8 / 5.4	8.1 / 6.5 / 5.8	9.6 / 8.1 / 6.5	11.3 / 9.6 / 6.5	13.0 / 11.3 / 9.6	16.0 / 14.4 / 13.0	19.8 / 17.6 / 15.7
	Heating	H/M/L m³/min	6.5 / 5.8 / 5.4	8.1 / 6.5 / 5.8	9.6 / 8.1 / 6.5	11.3 / 9.6 / 6.5	13.0 / 11.3 / 9.6	16.0 / 14.4 / 13.0	19.8 / 17.6 / 15.7
Sound Pressure		H/M/L dBA	34 / 33 / 32	36 / 35 / 33	37 / 35 / 34	39 / 37 / 34	40 / 38 / 37	42 / 41 / 40	43 / 41 / 40
Sound Power		H/M/L dBA	54 / 53 / 52	55 / 54 / 53	57 / 55 / 54	59 / 57 / 54	60 / 58 / 57	62 / 61 / 60	62 / 60 / 59
Dimensions	Body	WxDxH mm	882 x 260 x 450	882 x 260 x 450	882 x 260 x 450	882 x 260 x 450	882 x 260 x 450	882 x 260 x 450	882 x 260 x 450
Net Weight		kg(lbs)	26.0	26.0	26.0	26.0	26.5	26.5	27
Piping Connection	Liquid	mm(inch)	Ø6.35	Ø6.35	Ø6.35	Ø6.35	Ø6.35	Ø9.52	Ø9.52
	Gas	mm(inch)	Ø12.7	Ø12.7	Ø12.7	Ø12.7	Ø12.7	Ø15.88	Ø15.88
	Drain	I.D. mm(inch)	25	25	25	25	25	25	25
Fan motor output x Number		W	154 x 1	154 x 1	154 x 1	154 x 1	154 x 1	154 x 1	154

\* This product contains Fluorinated Greenhouse Gases.(R410A)

## Note :

1. Capacities are based on the following conditions

Cooling - Indoor temp. 27°C(80.6°F)DB / 19°C(66.2°F)WB  
Outdoor temp. 35°C(95°F)DB / 24°C(75.2°F)WB  
Interconnecting piping length 7.5m  
Level difference of zero

Heating - Indoor temp. 20°C(68°F)DB / 15°C(59°F)WB  
Outdoor temp. 7°C(44.6°F)DB / 6°C(42.8°F)WB  
Interconnecting piping length 7.5m  
Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification  
3. BH : The Sound Pressure test condition is based on 50 Pa (Static Pressue) as standard.  
4. ID - 'Internal Diameter'

## Accessories

Model	ARNU07GBHA4	ARNU09GBHA4	ARNU12GBHA4	ARNU15GBHA4	ARNU18GBHA4	ARNU24GBHA4	ARNU28GBHA4
Dry Contact	Simple (1 Contact point with case)			PDRYCB000			
	2 Contact point			PDRYCB400			
	For Thermostat (On-off / Mode / Fan speed)			PDRYCB300			
	Modbus Communication			PDRYCB500			

Wired Remote Controller					Wired Remote Controller
Premium	Standard II		Simple	Simple for Hotel	
PREMTA000 PREMTA000A PREMTA000B	PREMTB001 (White)	PREMTB001 (Black)	PQRCVLOQ (Black) PQRCVLOQW (White)	PQRCHCA0Q(Black) PQRCHCA0QW(White)	PQWRHQ0FDB