

4 WAY CASSETTE (570x570)

ARNU05GTRC4 / ARNU07GTRC4 / ARNU09GTRC4
ARNU12GTRC4 / ARNU15GTQC4 / ARNU18GTQC4 / ARNU21GTQC4



Model	Independent Unit		ARNU05GTRC4	ARNU07GTRC4	ARNU09GTRC4	ARNU12GTRC4	ARNU15GTQC4	ARNU18GTQC4	ARNU21GTQC4
Capacity	Cooling	Nom kW	1.6	2.2	2.8	3.6	4.5	5.6	6.0
	Heating	Nom kW	1.8	2.5	3.2	4.0	5.0	6.3	6.8
Power Input	Cooling	Nom W	30.0	30.0	30.0	30.0	30.0	30.0	30
	Heating	Nom W	30.0	30.0	30.0	30.0	30.0	30.0	30
Power Supply		Φ/V/Hz	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60	1/220-240/50,60
Airflow Rate	Cooling	H/M/L m³/min	7.5 / 7.0 / 6.6	7.5 / 7.0 / 6.6	8.0 / 7.5 / 7.1	8.7 / 8.0 / 7.0	11.0 / 10.0 / 9.3	11.2 / 11.0 / 10.0	12.0 / 11.1 / 9.4
	Heating	H/M/L m³/min	7.5 / 7.0 / 6.6	7.5 / 7.0 / 6.6	8.0 / 7.5 / 7.1	8.7 / 8.0 / 7.0	11.0 / 10.0 / 9.3	11.2 / 11.0 / 10.0	12.0 / 11.1 / 9.4
Sound Pressure		H/M/L dBA	29 / 27 / 26	29 / 27 / 26	30 / 29 / 27	32 / 30 / 27	36 / 34 / 32	37 / 35 / 34	42 / 40 / 35
Sound Power		H/M/L dBA	46 / 44 / 43	46 / 44 / 43	47 / 46 / 44	48 / 46 / 43	51 / 49 / 47	52 / 50 / 49	57 / 55 / 50
Dimensions	Body	WxHxDmm	570 x 214 x 570	570 x 214 x 570	570 x 214 x 570	570 x 214 x 570	570 x 256 x 570	570 x 256 x 570	570 x 256 x 570
Net Weight		kg	13.1	13.1	13.1	13.1	15.5	15.5	15
Piping Connection	Liquid	mm	6.35	6.4	6.35	6.4	6.35	6.35	9.52
	Gas	mm	12.7	12.7	12.7	12.7	12.7	12.7	15.88
	Drain	I.D mm	25	25	25	25	25	25	25
Decoration Panel	Model		PT-UQC	PT-UQC	PT-UQC	PT-UQC	PT-UQC	PT-UQC	PT-UQC
	Colour		Morning fog	Morning fog	Morning fog	Morning fog	Morning fog	Morning fog	Morning fog
	Dimensions	WxHxDmm	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700
	Weight	kg	3	3	3	3	3	3	2.8

* This product contains Fluorinated Greenhouse Gases(R410A)

Note :

1. Capacities are based on the following conditions

Cooling - Indoor temp. 27°C(80.6°F)DB / 19°C(66.2°F)WB
Outdoor temp. 35°C(95°F)DB / 24°C(75.2°F)WB
Interconnecting piping length 7.5m
Level difference of zero

Heating - Indoor temp. 20°C(68°F)DB / 15°C(59°F)WB
Outdoor temp. 7°C(44.6°F)DB / 6°C(42.8°F)WB
Interconnecting piping length 7.5m
Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification 3. I.D - 'Internal Diameter'

Accessories

Model	ARNU05GTRC4	ARNU07GTRC4	ARNU09GTRC4	ARNU12GTRC4	ARNU15GTQC4	ARNU18GTQC4	ARNU21GTQC4
Dry Contact	Simple (1 Contact point with case)				PDRYCB000		
	2 Contact point				PDRYCB400		
	For Thermostat (On-off / Mode / Fan speed)				PDRYCB300		
	Modbus Communication				PDRYCB500		
Front Panel				PT-UQC			
Ventilation Kit				PTVK430			

Wired Remote Controller					Wired Remote Controller
Premium	Standard II		Simple	Simple for Hotel	
PREMTA000 PREMTA000A PREMTA000B	PREMTB001 (White)	PREMTB01 (Black)	PQRCVCLQ (Black) PQRCVCLQW (White)	PQRCHCA0Q(Black) PQRCHCA0QW(White)	PQWRHQ0FDB